KPS™ 54 mm 1-1/2" Primary Piping

Pipe

Conductive petrol pipes with permeation barrier **Article Number** Description Remark Ø (mm) Length (m) Pipe 54 mm, 5.8 m lengths. KP 54EC6 Pipe 54 mm, conductive 54 348 m 60 units per package KP 54EC50 Pipe 54 mm, conductive Pipe 54 mm, 50 m coil 54 50 m KP 54EC100 Pipe 54 mm, conductive Pipe 54 mm, 100 m coil 54 100 m Approved according to EN 14125, German standard, EN 13463-1, IP2 and ATEX 137 (directive 1999/92/EC). **Conductive connectors for pipe joints** KP CC-54 Conductor 54 mm, conductive 54 50 Connectors used to bridge joints thereby maintaining conductivity throughout the pipe system. Patented design.

Welding Sockets



Article Number	Description	Remark	Ø (mm)	Pack Size
KP 2-54	Welding socket 54 mm		54	40
KP 2-54R	Welding socket 54 mm, no pipe stop	Slides over the pipe	54	1

Bends, Elbows and Tees





Article Number	Description	Remark	Ø (mm)	Pack Size
KP 3-54FC	Bend 90° 54 mm, conductive		54	10
KP 3-54FCL	Bend 90° 54 mm, conductive, long type	48 cm extra length	54	1
KP 4-54FC	Bend 45° 54 mm, conductive		54	20
Conductive tee	with permeation barrier			
KP 8-54FC02	Tee 54 mm, conductive	Equal tee	54	18

Entry Seals



Article Number	Description	Remark	Ø (mm)	Pack Size		
KP TM75/54	Entry seal, pipe 75/63/54 mm	Threaded, no bolts necessary. Use hole saw Ø 114 mm.	75/63/54	8		
KP M75/54	Entry seal, pipe 75 to 54 mm	Use hole saw Ø 92 mm.	75/63/54	15		
Blind entry s	Blind entry seal					
KP TM75/54B	Blind entry seal, pipe 75/63/54 mm	Threaded, no bolts necessary.	75/63/54	10		

Transition Fittings

emale trans				
Article Number	Description	Remark	Ø (mm)	Pack Size
KP C17-54F	Transition fitting 54 mm, steel	1½" BSPT female / Rc 1½"	54	15
Male transiti	on fittings, conductive, pla	stic to steel		
KP C17-54M	Transition fitting 54 mm, steel	1½" BSPT male / R ½"	54	15







Conductive stub flanges, DIN flanges and gaskets for pipe termination				
KP C20-54	Stub flange, DIN flange and gasket 54 mm, steel		54	4
KP W6-54	Separate threaded DIN flange 54 mm, steel	BSPT 1½" female / Rc 1½"	54	1



	Jee			
KP W6-54	Separate threaded DIN flange 54 mm, steel	BSPT 1½" female / Rc 1½"	54	1
Separate flange in stainless	steel available upon request			



Compressio	Compression transition fittings, conductive, plastic to steel					
KP C14-54M	Transition fitting 54 mm, brass	1½" BSPT male / R 1½"	54	1		
Flange fittir	ngs					



Flange fitting	js		
KP F16-54MM	Flange fitting	1½" BSPT male-male / R-R 1½"	1
KP F16-54MF	Flange fitting	11/2" BSPT male-female / R-Rc 11/2"	1
KP F16-54FF	Flange fitting	11/2" BSPT female-female / Rc-Rc 11/2"	1

Flexible Connectors and Valves

Conductive flexible connectors, union coupling



Article Number	Description	Remark	Length (mm)
KP T40-4S	Flex hose 400 mm, stainless	BSPT 1½" male x 1½" female union R 1½" x Rc 1½" union	400
KP T40-6S	Flex hose 600 mm, stainless	BSPT 1½" male x 1½" female union R 1½" x Rc 1½" union	600
KP T40-13S	Flex hose 1300 mm, stainless	BSPT 1½" male x 1½" female union R 1" x Rc 1" union	1300

Conductive flexible connectors, hexagon nipple type



	· · · · · · · · · · · · · · · · · · ·	1.1	
KPTN40-3S	Flex hose 300 mm, stainless	BSPT 1½" male x male / R 1½" x R 1½"	300
KP TN40-4S	Flex hose 400 mm, stainless	BSPT 1½" male x male / R 1½" x R 1½"	400
KP TN40-6S	Flex hose 600 mm, stainless	BSPT 1½" male x male / R 1½" x R 1½"	600
KP TN40-10S	Flex hose 1000 mm, stainless	BSPT 1½" male x male / R 1½" x R 1½"	1000
KP TN40-13S	Flex hose 1300 mm, stainless	BSPT 1½" male x male / R 1½" x R 1½"	1300
Valves			



KP 14-040	Ball valve 1½"	BSPT 1½" female / Rc 1½"	1