

Pipe

KPS™ 63 mm 2" Primary Piping



Conductive petrol pipes with permeation barrier

Article Number	Description	Remark	Ø (mm)	Length (m)
KP 63EC6	Pipe 63 mm, conductive	Pipe 63 mm, 5.8 m lengths. 48 units per package	63	278 m
KP 63EC50	Pipe 63 mm, conductive	Pipe 63 mm, 50 m coil	63	50 m
KP 63EC85	Pipe 63 mm, conductive	Pipe 63 mm, 85 m coil	63	85 m

Approved according to EN 14125, German standard, EN 13463-1, IP2 and ATEX 137 (directive 1999/92/EC).

Conductive connectors for pipe joints

KP CC-63	Conductor 63 mm, conductive		63	45
----------	-----------------------------	--	----	----

Connectors used to bridge joints thereby maintaining conductivity throughout the pipe system. Patented design.

Welding Sockets



Article Number	Description	Remark	Ø (mm)	Pack Size
KP 2-63	Welding socket 63 mm		63	45
KP 2-63R	Welding socket 63 mm, no pipe stop	Slides over the pipe	63	1

Bends, Elbows and Tees

Conductive formed bends and elbows with permeation barrier

Article Number	Description	Remark	Ø (mm)	Pack Size
KP 3-63FC	Bend 90° 63 mm, conductive		63	8
KP 3-63FCL	Bend 90° 63 mm, conductive, long type	50 cm extra length	63	1
KP 4-63FC	Bend 45° 63 mm, conductive		63	20

Conductive weldable elbows

KP 23-63EC	Elbow 90° 63 mm, conductive	Weldable	63	10
KP 24-63EC	Elbow 45° 63 mm, conductive	Weldable	63	12

Conductive tee with permeation barrier

KP 28-63EC	Tee 63 mm, conductive	Weldable	63	10
------------	-----------------------	----------	----	----

Entry Seals



Article Number	Description	Remark	Ø (mm)	Pack Size
KP TM75/54	Entry seal, pipe 75/63/54 mm	Threaded, no bolts necessary. Use hole saw Ø 114 mm.	75/63/54	8
KP M75/54	Entry seal, pipe 75 to 54 mm	Use hole saw Ø 92 mm.	75/63/54	15
KP TM63-B	Entry seal, pipe 63 mm	Use hole saw Ø 114 mm.	63	8



Blind entry seal

Article Number	Description	Remark	Ø (mm)	Pack Size
KP TM75/54B	Blind entry seal, pipe 75/63/54 mm	Threaded, no bolts necessary. Use hole saw Ø 114 mm.	75/63/54	10

Transition Fittings

Female transition fittings, conductive, plastic to steel

Article Number	Description	Remark	Ø (mm)	Pack Size
KP C17-63F	Transition fitting 63 mm, steel	2" BSPT female / Rc 2"	63	12
KP C17-63/54F	Transition fitting 63/54 mm, reduced, steel	1½" BSPT female / Rc 1½"	63/54	12
KP C17-63FL	Transition fitting 50 cm stub, 63 mm, steel	2" BSPT female / Rc 2"	63	10
KP C17-63/54FL	Transition fitting 50 cm stub, 63/54 mm, reduced, steel	1½" BSPT female / Rc 1½"	63/54	10

Male transition fittings, conductive, plastic to steel

KP C17-63M	Transition fitting 63 mm, steel	2" BSPT male / R 2"	63	12
KP C17-63ML	Transition fitting 50 cm stub, 63 mm, steel	2" BSPT male / R 2"	63	10
KP C17-63/54ML	Transition fitting 50 cm stub, 63/54 mm, reduced, steel	1½" BSPT male / R 1½"	63/54	10

Female transition flange fittings, with spacer, conductive, plastic to steel

KP C16-63F	Transition fitting 63 mm, steel	2" BSPT female / Rc 2"	63	10
KP C16-63/54F	Transition fitting 63/54 mm, reduced, steel	1½" BSPT female / Rc 1½" steel	63/54	10
KP C16-63FL	Transition fitting 50 cm stub 63 mm, steel	2" BSPT female / Rc 2"	63	1

Male transition flange fittings, with spacer, conductive, plastic to steel

KP C16-63M	Transition fitting 63 mm, steel	2" BSPT male / R 2"	63	10
KP C16-63/54M	Transition fitting 63/54 mm, reduced, steel	1½" BSPT male / R 1½"	63/54	10
KP C16-63ML	Transition fitting 50 cm stub, 63 mm, steel	2" BSPT male / R 2"	63	1

Conductive stub flanges, DIN flanges and gaskets for pipe termination

KP C20-63	Stub flange, DIN flange and gasket 63 mm, steel		63	4
KP C20-63L	Stub flange, 50 cm stub, DIN flange and gasket 63 mm, steel		63	1
KP W6-63	Separate threaded DIN flange 63 mm, steel	BSPT 2" female / Rc 2"	63	1

Separate flange in stainless steel available upon request

Compression transition fittings, conductive, plastic to steel

KP C14-63M	Transition fitting 63 mm, brass	2" BSPT male / R 2"	63	1
KP C14-63MS	Transition fitting 63 mm, stainless steel	2" BSPT male / R 2" Extended delivery time may apply.	63	1
KP C14-63/54M	Transition fitting 63/54 mm, reduced, brass	1½" BSPT male / R 1½"	63	1
KP C14-63/25M	Transition fitting 63/25 mm, reduced, brass	1" BSPT male / R 1"	63	1

Flange fittings

KP F16-63MM	Flange fitting	2" BSPT male-male / R-R 2"		1
KP F16-63MF	Flange fitting	2" BSPT male-female / R-Rc 2"		1
KP F16-63FF	Flange fitting	2" BSPT female-female / Rc-Rc 2"		1

Flexible Connectors and Valves

Conductive flexible connectors, union coupling

Article Number	Description	Remark	Length (mm)
KP T50-4S	Flex hose 400 mm, stainless	BSPT 2" male x 2" female union R 2" x Rc 2" union	400
KP T50-6S	Flex hose 600 mm, stainless	BSPT 2" male x 2" female union R 2" x Rc 2" union	600
KP T50-8S	Flex hose 800 mm, stainless	BSPT 2" male x 2" female union R 2" x Rc 2" union	800
KP T50-12S	Flex hose 1200 mm, stainless	BSPT 2" male x 2" female union R 2" x Rc 2" union	1200



Conductive flexible connectors, hexagon nipple type

KP TN50-4S	Flex hose 400 mm, stainless	BSPT 2" male x male / R 2" x R 2"	400
KP TN50-6S	Flex hose 600 mm, stainless	BSPT 2" male x male / R 2" x R 2"	600



Valves

KP 14-050	Ball valve 2"	BSPT 2" female / Rc 2"	1
KP 15-050	Shut-off valve 2"	BSPT 2" female / Rc 2"	1
KP 15-050HL	Shut-off valve handle	To open and close shut-off valve from surface level.	1



AdBlue Fittings

Article Number	Description	Remark	Ø (mm)	Pack Size
KP C14-63MS	Transition fitting 63 mm, stainless steel	2" BSPT male / R 2"	63	1



Extended delivery time may apply on stainless steel fittings.